

Link do produktu: <https://www.aquatech.fun/blok-zeglarski-master-pe-0202f-p-38.html>

# Blok żeglarski MASTER PE-0202F



Dostępność

Na zamówienie

## Opis produktu

| Item No.  | Description             | Sheave |    | Length |    | Weight |     | Max line size |    | Safe working load |     | Breaking load |     |
|-----------|-------------------------|--------|----|--------|----|--------|-----|---------------|----|-------------------|-----|---------------|-----|
|           |                         | in     | mm | in     | mm | oz     | g   | in            | mm | lb                | kg  | lb            | kg  |
| BB-0201F  | Single/Swivel           | 1 1/8  | 29 | 2 3/5  | 66 | 0.88   | 25  | 5/18          | 8  | 352               | 160 | 1102          | 500 |
| BB-0202F  | Single/Swivel/Becket    | 1 1/8  | 29 | 3      | 78 | 0.95   | 27  | 5/18          | 8  | 352               | 160 | 1102          | 500 |
| BB-0203F  | Double/Swivel           | 1 1/8  | 29 | 2 3/5  | 66 | 1.52   | 43  | 5/18          | 8  |                   | 320 |               | 800 |
| BB-0204F  | Double/Swivel/Becket    | 1 1/8  | 29 | 3      | 78 | 1.62   | 46  | 5/18          | 8  |                   | 320 |               | 800 |
| BB-0205F  | Triple/Swivel           | 1 1/8  | 29 | 2 3/5  | 66 | 2.05   | 58  | 5/18          | 8  |                   | 480 |               | 960 |
| BB-0206F  | Triple/Swivel/Becket    | 1 1/8  | 29 | 3      | 78 | 2.12   | 60  | 5/18          | 8  |                   | 480 |               | 960 |
| BB-0212F  | Triple/Cam              | 1 1/8  | 29 | 2 5/7  | 69 | 3.18   | 90  | 5/18          | 8  | 176               | 80  | 352           | 160 |
| BB-0212FE | Triple/Cam/Angle        | 1 1/8  | 29 | 2 5/7  | 69 | 3.42   | 97  | 5/18          | 8  | 176               | 80  | 352           | 160 |
| BB-0213F  | Triple/Cam/Becket       | 1 1/8  | 29 | 3      | 78 | 3.25   | 92  | 5/18          | 8  | 176               | 80  | 352           | 160 |
| BB-0213FE | Triple/Cam/Angle/Becket | 1 1/8  | 29 | 3      | 78 | 3.46   | 98  | 5/18          | 8  | 176               | 80  | 352           | 160 |
| BB-0215F  | Single                  | 1 1/8  | 29 | 2      | 53 | 0.6    | 17  | 5/18          | 8  | 352               | 160 | 1102          | 500 |
| BB-0217F  | Stand-up                | 1 1/8  | 29 | 2      | 53 | 0.92   | 26  | 5/18          | 8  | 352               | 160 | 1102          | 500 |
| BB-0209F  | Cheek                   | 1 1/8  | 29 | 2 1/6  | 55 | 0.56   | 16  | 5/18          | 8  | 352               | 160 | 1102          | 500 |
| BB-0216F  | Lashing                 | 1 1/8  | 29 | 1 3/4  | 44 | 0.53   | 15  | 5/18          | 8  | 352               | 160 | 1102          | 500 |
| BB-0223F  | 90° Fixed head          | 1 1/8  | 29 | 2      | 53 | 0.81   | 23  | 5/18          | 8  | 352               | 160 | 1102          | 500 |
| BB-0214F  | Connected               | 1 1/8  | 29 | 3 1/2  | 90 | 1.24   | 35  | 5/18          | 8  | 352               | 160 | 1102          | 500 |
| PE-0201F  | Swivel exit/Cam         | 1 1/8  | 29 | 3 3/4  | 70 | 4.77   | 136 | 5/18          | 8  | 352               | 160 | 1102          | 500 |
| PE-0201FE | Swivel exit/Cam/Angle   | 1 1/8  | 29 | 3 3/4  | 70 | 6.44   | 183 | 5/18          | 8  | 176               | 80  | 352           | 160 |