

Link do produktu: <https://www.aquatech.fun/hl-0501f-p-352.html>

HL-0501F



Dostępność

Na zamówienie

Opis produktu

Item No.	Description	Sheave		Length		Weight		Max line size		Safe working load		Breaking load	
		in	mm	in	mm	oz	g	in	mm	lb	kg	lb	kg
HL-0501F	Upright Lead	2 1/4	57	4	78	5.29	150	3/8	10	2640	1200	5500	2500
HL-0701F	Upright Lead	3	76	4 1/7	105	11.29	320	1/2	12	5060	2300	10120	4600
HL-4501F	Single/Halyard	1 3/4	45	3	76	5.11	145	3/8	10	2640	1200	5500	2500
HL-0502F	Single/Halyard	2 1/4	57	3 1/4	82	9.88	280	3/8	10	2640	1200	5500	2500
HL-0503F	Double/Halyard	2 1/4	57	3 1/4	82	14.82	420	3/8	10	2640	1200	5500	2500
HL-0504F	Triple/Halyard	2 1/4	57	3 1/4	82	5.64	160	3/8	10	2640	1200	5500	2500
FF-0502F	Pivoting Lead	2 1/4	57	4 4/7	116	5.70	161	3/8	10	2640	1200	5500	2500
FF-0702F	Pivoting Lead	3	75	5 5/7	145	10.09	286	3/8	10	5060	2300	10120	4600
FF-0501F	Pivoting Lead/Cam	2 1/3	57	4 4/7	116	9.79	277	3/8	10	330	150	770	350
FF-0701F	Pivoting Lead/Cam	3	75	5 5/7	145	15.90	442	3/8	10	330	150	770	350
FF-0501FE	Pivoting Lead/Cam/Angle	2 1/4	57	4 4/7	116	10.07	285	3/8	10	330	150	770	350
FF-0701FE	Pivoting Lead/Cam/Angle	3	75	5 5/7	145	16.01	454	7/16	12	330	150	770	350