

Link do produktu: <https://www.aquatech.fun/hl-0502f-p-353.html>



HL-0502F

Cena brutto	840,00 zł
Cena netto	682,93 zł
Dostępność	Na zamówienie

Opis produktu

Item No.	Description	Sheave		Length		Weight		Max line size		Safe working load		Breaking load	
		in	mm	in	mm	oz	g	in	mm	lb	kg	lb	kg
HL-0501F	Upright Lead	21/4	57	4	78	5.29	150	3/8	10	2640	1200	5500	2500
HL-0701F	Upright Lead	3	76	41/7	105	11.29	320	1/2	12	5060	2300	10120	4600
HL-4501F	Single/Halyard	13/4	45	3	76	5.11	145	3/8	10	2640	1200	5500	2500
HL-0502F	Single/Halyard	21/4	57	31/4	82	9.88	280	3/8	10	2640	1200	5500	2500
HL-0503F	Double/Halyard	21/4	57	31/4	82	14.82	420	3/8	10	2640	1200	5500	2500
HL-0504F	Triple/Halyard	21/4	57	31/4	82	5.64	160	3/8	10	2640	1200	5500	2500
FF-0502F	Pivoting Lead	21/4	57	44/7	116	5.70	161	3/8	10	2640	1200	5500	2500
FF-0702F	Pivoting Lead	3	75	55/7	145	10.09	286	3/8	10	5060	2300	10120	4600
FF-0501F	Pivoting Lead/Cam	21/3	57	44/7	116	9.79	277	3/8	10	330	150	770	350
FF-0701F	Pivoting Lead/Cam	3	75	55/7	145	15.90	442	3/8	10	330	150	770	350
FF-0501FE	Pivoting Lead/Cam/Angle	21/4	57	44/7	116	10.07	285	3/8	10	330	150	770	350
FF-0701FE	Pivoting Lead/Cam/Angle	3	75	55/7	145	16.01	454	7/16	12	330	150	770	350